




备注：侧弹分为外弹与内弹

NOTES:
Housing: Thermoplastics
Contact: Copper Alloy
Shell: Copper Alloy/Steel
Voltage Current Rating:1.5 AMP. 30V AC
Insulation Resistance:1000MΩ Min.
Contact Resistance:30 MΩ Max.
Dielectric Withstanding Voltage:500W AC
Temperature Range: -35℃ to +85℃
Insulator color: Black/White
Plastic material:PBT/LCP/Others
Shell finish:Nickel plated/Tin-Lead plated
Me il:
Ma rce:3.5KG MAX
Un Force:0.7 KG MIN.
Co i nish:
ctive Gold Flash
ective Gold 3U"
03:Selective Gold 5U"
04:Selective Gold 15U"
05:Selective Gold 30U"

产品图 PRODUCT CHART DWG		易芯精密科技(浙江)有限公司 Easychips Precision Technology (Zhejiang) Co.,Ltd.					
公差一览表 TOLERANCE UNLESS OTHERWISE		单位 UNITS	MM	制图 DRAWING	Z-Y-B	产品料号 PRODUCT PART NO.	A904-EC131A2032S10100
X.	±0.25	X'.	±5'	比例 SCALE	1:1	审核 CHKD	产品名称 PRODUCT NO.
.X	±0.20	.X'	±2'	日期 DATE	2015.06.20	核准 APPD	角法 VIEW
.XX	±0.15	.XX'	±1'				版本 VER
.XXX	±0.10	.XXX'	±0.5'				A0