



RoHS

MAPX





MODIFICATION

DRW

DATE



RECOMMENDED PCB LAYOUT



NOTE

1.MATERIAL

HOUSING: THERMOPLASTIC
SHELL: SPCC OR COPPER ALLOY
CONTACT: COPPER ALLOY

2.ELECTRICAL PERFORMANCE:

- 2.1 CURRENT: 2A MIN
2.2 CONTACT RESISTANCE: 30mOHMS MAX.
2.3 DIELECTRIC STRENGTH
UNMATED: 500V AC RMS
2.4 INSULATION RESISTANCE: 100MOHMS MIN

3.MECHANICAL PERFORMANCE:

- 3.1 INSERTION FORCE: 35N MAX.
3.2 WITHDRAWAL FORCE: 4N MIN
35N MAX.
3.3 TEMPERATURE RANGE: -25°C TO 85°C

产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

X.	±0.25	X.	±5°
.X	±0.20	.X	±2°
.XX	±0.15	.XX	±1°
.XXX	±0.05	.XXX	±0.5°



易芯精密科技(浙江)有限公司

Easychips Precision Technology (Zhejiang) Co., Ltd.

单位 UNITS	MM	制图 DRAWING	制图料号 PRODUCT PART NO.	A906-EC862A3119D102WD
比例 SCALE	1:1	审核 CHKD	产品名称 PRODUCT NO.	AF11.8侧插外鱼叉内0型脚无边铜壳PA9T橙胶5PIN
日期 DATE	2021-04-12	核准 APPD	角法 VIEW	版本 VER
				A0