







A  
B  
C  
D  
E  
F  
G

1 2 3 4 5 6 7 8 9 10

|      |              |      |
|------|--------------|------|
| MAPX | MODIFICATION | DATE |
|      |              |      |



PCB LAYOUT T=2.1mm(max)  
TOP VIEW TOLERANCE:±0.1mm  
2层或以上PCB板建议布线方式



PCB LAYOUT T=2.1mm(max)  
TOP VIEW TOLERANCE:±0.1mm  
单层板建议布线方式

NOTES:

1.MATERIAL:

- 1.1 HOUSHING: THERMOPLASTIC COLOR:BLACK
- 1.2 CONTACT: COPPER ALLOY
- 1.3 SHELL: STAINLESS STEEL OR K7

2. PLATING;

CONTACT:

- 1). GOLD FLASH CONTACT AREA;120u" TIN SOLDER;NICKEL OVER ALL
- 2). 5u" GOLD CONTACT AREA;120u" TIN SOLDER;NICKEL OVER ALL
- 3). 15u" GOLD CONTACT AREA;120u" TIN SOLDER;NICKEL OVER ALL

SHELL: NICKEL OVER ALL

4.ENVIRONMENTAL:

OPERATION TEMPERATURE: -40° C~+85° C

5.PRODUCT COMPLIANT TO THE REQUEST OF RoHS

产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

|      |       |      |       |
|------|-------|------|-------|
| X.   | ±0.25 | X.   | ±5°   |
| .X   | ±0.20 | .X   | ±2°   |
| .XX  | ±0.15 | .XX  | ±1°   |
| .XXX | ±0.10 | .XXX | ±0.5° |



易芯精密科技(浙江)有限公司  
Easychips Precision Technology (Zhejiang) Co., Ltd.

|             |            |               |  |                          |                                |
|-------------|------------|---------------|--|--------------------------|--------------------------------|
| 单位<br>UNITS | MM         | 制图<br>DRAWING |  | 制图料号<br>PRODUCT PART NO. | A909-EC161C2021D10100          |
| 比例<br>SCALE | 1:1        | 审核<br>CHKD    |  | 产品名称<br>PRODUCT NO.      | AF90度12.0双面插直脚无边铁壳LCP黑胶6.45 8P |
| 日期<br>DATE  | 2021-04-13 | 核准<br>APPD    |  | 角法<br>VIEW               | 版本<br>VER                      |
|             |            |               |  |                          | AO                             |