



MAPX	MODIFICATION	DATE

- Note:
- Material: 
 - Housing: High temperature thermoplastic with g.f,UL94v-0
 - Contact: copper alloy,t=0.20mm
 - Shell: copper alloy,t=0.25mm
- 2.Specification:
- Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.
 - Dielectric withstanding voltage: 100 V(ac) for 1 min.
 - Contact resistance: 30 mΩ Max.
 - Insulation resistance: 100 MΩ Min.
 - Total mating force: 3.57 Kgf Max.
 - Total unmating force: 1.0 Kgf Min.
 - Temperature range: -30°C~80°C

RECOMMENDED PCB LAYOUT
PCB图仅供参考

<p>产品图 PRODUCT CHART DWG</p>		 <p>易芯精密科技(浙江)有限公司 Easychips Precision Technology (Zhejiang) Co., Ltd.</p>			
<p>公差一览表 TOLERANCE UNLESS OTHERWISE</p>		<p>单位 UNITS</p>	<p>制图 DRAWING</p>	<p>制图料号 PRODUCT PART NO.</p>	<p>B920-ECC52A2021S10112</p>
.X	±0.30	X.	±5.°	<p>产品名称 PRODUCT NO.</p>	<p>MICRO 5S B型5.9两脚长1.25插板 有边有柱加焊脚SMT短端</p>
.X	±0.25	.X	±2.°		
.XX	±0.20	.XX	±1.°	<p>角法 VIEW</p>	<p>版本 VER</p>
.XXX	±0.10	.XXX	±0.5°	<p>日期 DATE</p>	<p>2019.11.23</p>
			<p>核淮 APPD</p>		<p>AO</p>