



MAPX	MODIFICATION	DATE

- Note:
- Material:
    - Housing: High temperature thermoplastic with g.f,UL94v-0
    - Contact: copper alloy,t=0.20mm
    - Shell: copper alloy,t=0.25mm
  - Specification:
    - Current rating:1.5PIN 1.8A Max/2,3,4PIN 1A Max.
    - Dielectric withstanding voltage: 100 V(ac) for 1 min.
    - Contact resistance: 30 mΩ Max.
    - Insulation resistance: 100 MΩ Min.
    - Total mating force: 3.57 Kgf Max.
    - Total unmating force: 1.0 Kgf Min.
    - Temperature range: -30°C~80°C

RECOMMENDED PCB LAYOUT PCB图仅供参考

<b>产品图</b> PRODUCT CHART DWG		<b>易芯精密科技(浙江)有限公司</b> Easychips Precision Technology (Zhejiang) Co.,Ltd.			
<b>公差一览表</b> TOLERANCE UNLESS OTHERWISE		单位 UNITS	MM	制图 DRAWING	制图料号 PRODUCT PART NO.
X.	±0.30	X.	±5.°	比例 SCALE	产品名称 PRODUCT NO.
.X	±0.25	.X	±2.°		
.XX	±0.15	.XX	±1.°	日期 DATE	角法 VIEW
.XXX	±0.10	.XXX	±0.5°		
2019.11.23		核准 APPD		制图料号 B920-ECC54A2021S10101	产品名称 MICRO 5S B型5.9两脚插板有边不锈钢有柱加焊脚SMT端子长0.75
2019.11.23		核准 APPD		角法 VIEW	版本 VER