



MAPX	MODIFICATION	DATE



Note:

1.Material:

1.1 Housing: High temperature thermoplastic with g.f,UL94v-0

1.2 Contact: copper alloy,t=0.20mm

1.3 Shell: copper or sus304,t=0.25mm

2.Specification:

2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.

2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.

2.3 Contact resistance: 30 mΩ Max.

2.4 Insulation resistance: 100 MΩ Min.

2.5 Total mating force: 3.57 Kgf Max.

2.6 Total unmating force: 1.0 Kgf Min

2.7 Temperature range: -30°C~80°C

<b>产品图</b> PRODUCT CHART DWG		<b>易芯精密科技(浙江)有限公司</b> Easychips Precision Technology (Zhejiang) Co., Ltd.				
<b>公差一览表</b> TOLERANCE UNLESS OTHERWISE		单位 UNITS	MM	制图 DRAWING	制图料号 PRODUCT PART NO.	B920-ECD62A2021S10101
X.	±0.30	X.	±5.°	比例 SCALE	产品名称 PRODUCT NO.	MICRO 5S B型两脚贴板无边有柱加焊脚 端子加长0.4
.X	±0.25	.X	±2.°	日期 DATE	角法 VIEW	版本 VER
.XX	±0.15	.XX	±1.°	2021-04-16	核淮 APPD	AO
.XXX	±0.10	.XXX	±0.5°			