



MAPX

MODIFICATION

DATE

NOTE:

1.MATERIAL SPECIFICATION:

1.HOUSING&PICKUP COVER:LCP,UL94 V-0.BLACK

2.CONTACTS:SEE TABLE 1

3.LATCH: STAINLESS STEEL(SUS301)

4.SPRING: STAINLESS STEEL(SUS304)

5.FRONT SHELL: STAINLESS STEEL(SUS304)

2.PLATING SPECIFICATION:

2-1.CONTACTS:

Ni 50u" MIN. UNDER PLATED OVER ALL.

Au PLATED ON THE FUNCTIONAL AREA OF CONTACT.

(GOLD PLATING THICKNESS FOLLOW THE P/N)

PLATING SPECIFICATIONS OF THE SOLDER AREA FOLLOW THE P/N

2-2.FRONT SHELL:

Ni 30u" MIN. UNDER PLATED OVER ALL.

2-3.LATCH:

Ni 50u" MIN. UNDER PLATED OVER ALL.

80u" MIN. TIN PLATED ON SOLDER AREA.

2-4.SPRING:

CLEAR ONLY

3.MECHANICAL PERFORMANCE,

3-1.INSERTION FORCE: 0.5~2.0kgf.

3-2.REMOVAL FORCE: 0.8kgf~2.0kgf.

3-3.DURABILITY: 10000 CYCLES.

4.ELECTRICAL PERFORMANCE,

4-1. CURRENT RATING:SEE TABLE 1

VOLTAGE RATING:5.0V

4-2. LLCR:

VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN M-X.

SHIELD: 50mΩ/MAX.

LLCR MAX. CHANGE OF ALL PINS: 10mΩ.

4-3.INSULATION RESISTANCE: 100MΩ MIN

4-4.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1 MINUTE.

5. ENVIRONMENTAL PERFORMANCE:

OPERATING TEMPERATURE: -25℃~+85℃.

6.IR REFLOW:

THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260°C.

产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

X.	±0.30	X.	±5.°
.X	±0.25	.X	±2.°
.XX	±0.15	.XX	±1.°
.XXX	±0.10	.XXX	±0.5°



易芯精密科技(浙江)有限公司
Easychips Precision Technology (Zhejiang) Co., Ltd.

单位 UNITS	MM	制图 DRAWING	GR	制图料号 PRODUCT PART NO.	C918-EC118A2021Y40000
比例 SCALE	1:1	审核 CHKD	GT	产品名称 PRODUCT NAME	TYPE-C3.1 公头180度直立11.1三支脚SMT间距0.9 LCP黑胶24PIN
日期 DATE	2021-05-06	核准 APPD	ZY	角法 VIEW	版本 VER
					AD