







A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

1. CURRENT RATING: 3.0A MAX
2. VOLTAGE: 100 VAC
3. TEMPERATURE RANGE: -30 °C ~ 85 °C
4. CONTACT RESISTANCE: 40 MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
6. INSERTION FORCE : 5N~20N
7. UNMATING FORCE: 8N~20N
8. DURABILITY: 10,000 CYCLES



 易芯精密科技(浙江)有限公司 Easychips Precision Technology (Zhejiang) Co., Ltd.							
产品图 PRODUCT CHART DWG							
公差一览表 TOLERANCE UNLESS OTHERWISE				单位 UNITS	制图 DRAWING	ZY	制图料号 PRODUCT PART NO
X.	±0.35	X.	±5.°	比例 SCALE	审核 CHKD	GR	产品名称 PRODUCT NAME
.X	±0.25	.X	±2.°	日期 DATE	核准 APPD	GT	角法 VIEW
.XX	±0.20	.XX	±1.°	2021-04-15			 版本 VER
.XXX	±0.10	.XXX	±0.5°				 A0